

SAFETY DATA SHEET

2020-8-8

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910. 1200.

U.S. Department of Labor Occupational Safety and Health Administration

(Non-Mandatory Form)

Standard must be consulted for specific requirements. Form Approved OMB No.1218-0072

§ 1 - IDENTITY INFORMATION

Product Name (as used on label and list): HOLBEIN ACRYLIC INK (HAI)

Manufacturer: HOLBEIN Works, Ltd.

Address: 2-2-5, Ueshio, Chuo-ku, Osaka-shi

OSAKA 542-0064 JAPAN

Telephone Number for information: 81-6-6191-7722 Emergency Telephone Number: 81-72-985-1221

Preparer: ALAKI, Yutaka

§ 2 - HAZARD IDENTIFICATION

This product is water-based and not classified as dangerous for supply or conveyance. The ingredients are water-reducible and falls well within the acceptable safety limits.

Classification: Non-regulated Danger: Nonflammable

Hazard information: Especially none (cf. § 11 - Toxicological Information)

Ecological consideration: Especially none

GHS label elements: Void

§ 3 - COMPOSITION / INGREDIENTS

Substance/Mixture: Mixture (*, ** and *** are Main Ingredients.)

Components (Specific Chemical Identity, Common Name(s)) CAS

Colorant * (Pigment / Table on catalogue)

Binder **(Alkaline Salt of Modified Acrylic Polymers)RegisteredMoisturizer(Propylene Glycol)57-55-6Thickener(Polyacrylate)9003-01-4Dispersant(Modified Copolymer)Registered

Water ***

§ 4 - FIRST AID MEASURES

Eyes: In case of eye contact, never rub. Rinse with plenty of water and if necessary consult

an eye specialist.

Skin: Upon skin contact, wash with plenty of water, soap or other non-irritating cleansing

igents.

Ingestion: In case of swallowing, drink plenty of water. Induce vomiting.

If you feel unwell, seek medical advice.

Inhalation: Upon inhalation of aerosol/vapor/dust, take the person to fresh air.

If there is difficulty in breathing, medical advice is required.

§ 5 - FIRE AND EXPLOSION HAZARD DATA

Flammability: Not combustible

Flash Point, Ignition Point: N/A

Combustion Products: Carbon dioxide and oxide of metal according to pigment or ash.

§ 6 - ACCIDENTAL RELEASE MEASURES

Especially none

§ 7 - HANDLING AND STORAGE

Precautions for Handling: Especially none. Wash mouth or hands after use.

Precautions for Storing and Transport: Especially none

§ 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Avoid invasion to the eyes or body. Avoid prolonged or repeated contact with skin.

§ 9 - PHYSICAL / CHEMICAL CHARACTERISTICS

Appearance: Colored Liquid

Odor: Faint acrylic odor with ammonium smell

Specific Gravity (H₂O = 1): $1.02 \sim 1.38$ (Av. 1.09)

Boiling Point: Same as water

Vapor Density (Air = 1): ---

Vapor Pressure (Butyl Acetate = 1): Same as water

pH: ca. 7.5

Solubility in Water : ∞ . Not so, after dried.

§ 10 - HAZARD INFORMATION AND STABILITY

Stability: Inert and stable under normal state

Incompatibility (Materials to Avoid): None

Hazardous Decomposition or Byproducts: No thermal decomposition when stored and handled

correctly.

§ 11 - TOXICOLOGICAL INFORMATION

Primary Routes of Entry: Dermal, eye contact, inhalation, swallowing

Eye irritation: Irritant, and may induce keratitis, but essentially not damage the

organization.

Skin irritation: May irritate by repeated or prolonged contact, and may cause

inflammation.

Inhalation Toxicity: Although some of raw materials stimulate eyes and respiratory organs

with their vapor or mists under highly concentrated state, the toxic act of

this colors is not confirmed.

Oral Toxicity: The toxicity of this products is not confirmed.

§ 12 - ECOLOGICAL INFORMATION

Biodegradability: Not readily biodegradable.

Persistency: Not been confirmed.

Aquatic environment toxicity: Not expected to be toxic to aquatic environment.

Fish Toxicity: Not been certified.

§ 13 - DISPOSAL CONSIDERATIONS

Disposal Considerations: Dispose in accordance with national and/or local regulations.

§ 14 - TRANSPORT INFORMATION

UN Proper Shipping Name: Not applicable

UN Number: Not applicable

UN Hazard Class: Not applicable Packing Group: Not applicable ADR/RID: Not classified

ADR: Transportation of Dangerous Goods on Roads RID: Transportation of Dangerous Goods on Railways

§ 15 - REGULATORY INFORMATION

Danger Class: N/A. (Not flammable liquid)

Law: Fire law: ditto

Conforms to ACMI under ASTM D 4236, and is classified into AP genre of ACMI system (See the table of Appendix).

ACMI: The Art & Creative Materials Institute, Inc.

ASTM: ASTM International (Former "American Society for Testing and Materials")

AP: Approved Product: Contain no materials in sufficient quantities to be toxic or injurious to humans.

§ 16 - OTHER INFORMATION

Notice: All information contained herein is for references and guidance for normal use, and not for all conceivable conditions of handling and use. The responsibility for irregular use belongs to user individuals. All information are under our knowledge of today. All information may change according to circumstances.

APPENDIX

Table Information of Acrylic Ink

AP (Approved Product): Contain no materials in sufficient quantities to be toxic or injurious to humans.

	Hazardous	Classification	Name of Color Hazardous Classification
	ingredient		ingredient
Bamboo Green	_	AP	Phthalo Blue — AP
Burnt Sienna	_	AP	Phthalo Green — AP
Burnt Umber	_	AP	Phthalo Turquoise — AP
Cobalt Blue	_	AP	Primary Black — AP
Dioxazine Violet	_	AP	Primary Cyan — AP
Greenish Yellow	_	AP	Primary Magenta – AP
Hansa Yellow	_	AP	Primary White — AP
Hansa Yellow Le	mon —	AP	Primary Yellow — AP
Hooker's Green	_	AP	Pyrrole Orange – AP
Imidazolone Bro	wn –	AP	Pyrrole Red — AP
Imidazolone Yell	ow –	AP	Quinacridone Crimson — AP
Indanthrene Blue	-	AP	Quinacridone Gold — AP
Isoindolinone Yel	llow —	AP	Quinacridone Magenta — AP
Lamp Black	_	AP	Quinacridone Red — AP
Luminous Lemor	1 –	AP	Raw Sienna – AP
Luminous Opera	_	AP	Raw Umber — AP
Mauve	_	AP	Sap Green — AP
Naphthol Red De	eep —	AP	Sepia – AP
Naphthol Red Lig	gĥt —	AP	Shadow Green — AP
Nickel Azo Yello	w –	AP	Super Opaque White — AP
Oxide of Chromi	um —	AP	Titanium White — AP
Pearl Gold	_	AP	Ultramarine Blue — AP
Pearl Silver	_	AP	Viridian Hue — AP
Pearl White	_	AP	Yellow Ochre — AP